



On-Grid Inverter
with Energy Storage

Krypton 5000



Grid Feeding



Dual Output



Intelligent Load Management



Batteryless Operation



PAL Upto 9 Units

Models: Hybrid Infini V II 3KW-24V



Easy-to-install

- Pure sine wave output
- Self-consumption and Feed-in to the grid
- Programmable supply priority for PV, Battery or Grid



Reliable

- User-adjustable charging current and voltage
- Programmable multiple operation modes: Grid-tie, off-grid and grid-tie with backup



User-friendly

- Monitoring software for real-time status display and control
- Parallel operation up to 9 unit for 3KW models
- Battery Independent system

KNOX SERIES	Krypton 5000
MODEL	HYBRID INFINI V II 3KW-24V
Phase	1-phase in / 1-phase out
Maximum PV Input Power	5000W
Rated Output Power	3000 W
Maximum Charging Power	2880W
GRID-TIE OPERATION	
PV INPUT (DC)	
Nominal DC Voltage / Maximum DC Voltage	360 VDC / 450 VDC
Start-up Voltage / Initial Feeding Voltage	130VDC / 150 VDC
MPP Voltage Range	120 VDC ~ 430 VDC
Number of MPP Trackers / Maximum Input Current	1/ 18A
GRID OUTPUT (AC)	
Nominal Output Voltage	220/230/240 VAC
Output Voltage Range	184 - 264.5 VAC or 195.5 - 253 VAC (Selectable)
Nominal Output Current	13A
Power Factor	> 0.99
EFFICIENCY	
Maximum Conversion Efficiency (DC/AC)	95%
OFF-GRID OPERATION	
AC INPUT	
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC
Acceptable Input Voltage Range	90 - 280 VAC or 170 - 280 VAC
Frequency Range	50 Hz/60 Hz (Auto sensing)
Maximum AC Input Current	40 A
PV INPUT (DC)	
Maximum DC Voltage	450 VDC
MPP Voltage Range	120 VDC ~ 430 VDC
Number of MPP Trackers / Maximum Input Current	1/ 18 A
BATTERY MODE OUTPUT (AC)	
Nominal Output Voltage	220/230/240 VAC
Output Waveform	Pure sine wave
Efficiency (DC to AC)	93%
HYBRID OPERATION	
PV INPUT (DC)	
Nominal DC Voltage / Maximum DC Voltage	360 VDC / 450 VDC
Start-up Voltage / Initial Feeding Voltage	130VDC / 150 VDC
MPP Voltage Range	120 VDC ~ 430 VDC
Number of MPP Trackers / Maximum Input Current	1/ 18A
GRID OUTPUT (AC)	
Nominal Output Voltage	220/230/240 VAC
Output Voltage Range	184 - 264.5 VAC or 195.5 - 253 VAC (Selectable)
Nominal Output Current	13A
AC INPUT	
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC
Acceptable Input Voltage Range	90 - 280 VAC or 170 - 280 VAC
Maximum AC Input Current	40 A
BATTERY MODE OUTPUT (AC)	
Nominal Output Voltage	220/230/240 VAC
Efficiency (DC to AC)	93%
BATTERY & CHARGER	
Nominal DC Voltage	24 VDC
Maximum Solar Charging Current	60 A
Maximum AC Charging Current	60 A
Maximum Charging Current	60 A
GENERAL	
PHYSICAL	
Dimension, D x W x H (mm)	120 x 295 x 468
Net Weight (kgs)	11
INTERACE	
Parallel Function	Yes, 9 units
Communication Port	USB or RS-232/Dry Contact
ENVIRONMENT	
Humidity	0 ~ 90% RH (No condensing)
Operating Temperature	-10°C to 50°C

Product specifications are subject to change without further notice.